TATES OF DELIVERY

DEPARTMENT OF THE ARMY

NORTHERN WARFARE TRAINING CENTER 1060 GAFFNEY ROAD #9900 FORT WAINWRIGHT, ALASKA 99703-9900

APVR-WNW 23 February 2007

MEMORANDUM FOR RECORD

SUBJECT: Arctic Light Individual Training Program (ALIT) Course Management Plan (CMP)

- 1. Introduction. ALIT is the United States Army Alaska's Cold Weather Indoctrination (CWI) program. USARAK Soldiers live, work, and play in one of the harshest environments in the world. USARAK Soldiers must possess the necessary skills to train to go to war in this demanding environment, despite these conditions. All leaders in USARAK have the inherent responsibility to prepare themselves and their Soldiers, both mentally and physically, to operate in the cold weather environment. The Arctic Light Individual Training (ALIT) program gives all Soldiers, regardless of their job, the foundation to successfully work and train in the environmental conditions typical of Alaska.
- a. This course management plan provides unit leaders and trainers with the information required to conduct the Arctic Light Individual Training Program (ALIT).
- b. This CMP is approved by the Commandant United States Army Alaska Northern Warfare Training Center and must be used when providing education, training and evaluation of this course. Provide any feedback to the course manager on the quality of the instruction, products and/or materials provided:

Commandant USANWTC ATTN: Training Administrator 1060 Gaffney Road, Building 1555 Ft. Wainwright, Alaska 99703-9900 907-353-1165

2. Table of Contents

Paragraph		
1	Introduction	1
2	Table of Contents	1
3	ALIT	2
3a	Course Purpose	2
3b	Course Scope	2
3c	Course Length	2
3d	Course Structure	2

SUBJECT: ALIT CMP

4	Ski and Snowshoe Training	8
5	References	9
6	Point of Contact	9
	Attachment 1: Sample Training Schedule	10
	Attachment 2: Packing List	12
	Attachment 3: Sample Memorandum Record of Training	14
	Attachment 4: Equipment and Resources Recommended	15
	Attachment 5: Student Evaluation Plan	17

3. ALIT.

- a. *Course Purpose*. To train all Soldiers, regardless of job function, in the skills required to successfully train and operate in a cold, snow-covered environment. Attendees will gain confidence in their cold weather clothing and equipment and their ability to care for themselves in the cold weather environment.
- b. *Course Scope*. Emphasis is placed on the effects of cold on personnel and materiel, recognition, treatment and prevention of cold weather injuries, use of basic cold weather clothing and equipment, winter field-craft, use of cold weather shelters, use of Army approved heaters, and over snow movement techniques. Cold weather risk management procedures are stressed throughout the course of instruction.
- c. *Course Length*. ALIT typically takes place over three days. A recommended ALIT training schedule is provided in Attachment 1. A recommended packing list in provided in Attachment 2. A recommended list of equipment and resources required for the training is in Attachment 4.

d. Course Structure. ALIT consists of:

- (1) Cold Weather Indoctrination I (CWI I). Classroom and basic skills instruction designed to introduce Soldiers to tactics, techniques and procedures for operating in the cold weather environment.
- (2) Cold Weather Indoctrination II (CWI II). Field instruction designed to give Soldiers experience and confidence working in the cold weather environment using equipment and clothing issued by the Army. This training must take place when the temperatures are 10 degrees Fahrenheit or colder. The intent of this temperature rating is to train Soldiers under the conditions that allow them to gain confidence in their equipment. Commanders will make every effort to meet this intent. Soldiers must spend two nights in the field:
- (a) Night one: Soldiers bivouac in the heated shelter they typically use in the field (e.g. 10 man Arctic tent and Space Heater Arctic).
- (b) Night two: Soldiers bivouac in an improvised shelter using only issued clothing and sleeping bag. No external sources of heat (stoves) will be used for warming except in emergencies. A warming shelter must be available for this training.

(3) A list of lessons plans used for the training is in Table 1 below. These lessons are available for download at $\frac{\text{http://www.wainwright.army.mil/nwtc/}}{\text{http://www.wainwright.army.mil/nwtc/}}$.

Table 1: ALIT Lessons						
	Cold Weather Indoctrination I					
Characteristics of	of Cold Regions					
LESSON#	699-80010					
ACTION	Analyze terrain in cold regions					
CONDITION	In a field or classroom environment, given a map sheet(s) of the training area					
STANDARD	Soldier: - Utilized OCOKA to conduct a thorough analysis of the training area Identified potential hazards associated with the mountain training area Used this information to manage risk during training.					
LESSON#	699-80011					
ACTION	Analyze weather of cold regions					
CONDITION	In a field or classroom environment, given an altimeter					
STANDARD	Soldier: - utilized various field techniques and procedures to predict weather. - identified potential hazards associated with the weather. - used this information to manage risk during training.					
	d Mountain Medical Considerations					
LESSON #	699-80013					
ACTION	Manage cold weather injuries					
CONDITION	Given the ECWCS, other issued cold weather clothing items, and issued cold weather sleep system with insulating pad, access to a warming shelter, under field conditions where temperatures range from 40° F to – 60° F					
STANDARD	Soldier: -Identified all of the signs and symptoms of each type of cold weather injurySelected and applied the recommended treatment for the specified cold weather injuryDid not sustain a cold weather injury during the conduct of the course.					
LESSON#	699-80014					
ACTION	Manage altitude illness					
CONDITION	Under any field condition					
STANDARD	Soldier: -Identified all of the signs and symptoms of altitude sicknessSelected and applied the recommended treatment for the specified altitude sickness.					

LESSON#	699-80015					
ACTION	Manage common cold weather and mountain environmental injuries					
CONDITION	Given the ECWCS, other issued cold weather clothing items, and issued cold weather sleep system with insulating pad, access to a warming shelter, under field conditions where temperatures range from 40° F to – 60° F					
STANDARD	Soldier: -Identified all of the signs and symptoms of common cold weather and mountain environmental injuriesSelected and applied the recommended treatment for common cold weather and mountain environmental injuries.					
Cold Weather Clot	hing and Equipment					
LESSON #	699-80016					
ACTION	Wear cold weather clothing and equipment					
CONDITION	Given the ECWCS, other issued cold weather clothing items, and issued cold weather sleep system with insulating pad, under field conditions where temperatures range from 40° F to – 60° F					
STANDARD	Soldier used issued cold weather clothing and equipment to prevent cold weather injuries.					
Risk Management						
LESSON #	699-80017					
ACTION	Manage risk in the cold weather environment					
CONDITION	In a classroom environment and/or under any environmental condition, given the USARAK Pamphlet 385-4, Risk Management for Cold Weather Operations					
STANDARD	Soldier conducted thorough, written risk assessments IAW USARAK PAM 385-4, Risk Management for Cold Weather Operations.					
Planning Consider	rations for Over Snow Movement					
LESSON #	699-80012					
ACTION	Plan for over snow movement					
CONDITION	In a snow covered field environment					
STANDARD	Soldier planned a 5km movement for a squad sized element over snow covered terrain with a solution plus or minus one hour.					
	Military Equipment					
LESSON #	699-80031					
ACTION	Maintain vehicles in cold weather					
CONDITION	In temperatures of 32° F to -60 °F, given a military vehicle with technical manual to maintain and operate					
STANDARD	Soldier identified common problems with vehicles and took steps to reduce or eliminate problems caused by the cold before/during/after operations.					
LESSON#	699-80032					
ACTION	Maintain weapons in cold weather					
CONDITION	In temperatures of 32° F to -60 °F, given assigned weapon with technical manual to maintain and operate					
STANDARD	Soldier identified common problems with weapons and took steps to reduce or eliminate problems caused by the cold before/during/after operations.					

LESSON#	699-80033
ACTION	Maintain communications and computer equipment in cold weather
CONDITION	In temperatures of 32° F to -60 °F, given communications and computer equipment to maintain and operate
STANDARD	Soldier identified common problems with communications and computer equipment and took steps to reduce or eliminate problems caused by the cold before/during/after operations.

Tent and Stove I	Drill

ACTION	Conduct tent and stove drill					
CONDITION	Given a serviceable Ahkio group, complete with the standard equipment load, and an area large enough to set up the tent and stove group. Task will be performed with a squad/team of no less than 5 personnel.					
STANDARD	Squad: - set-up tent and readied stove for operation within 30 minutes met all critical performance measures IAW the student/instructor evaluation plan.					
LESSON#	699-80026					
ACTION	Use an H-45 stove					
CONDITION	Given a serviceable H-45 and an area large enough to set up the stove					
STANDARD	Individual soldier: - Operated the H-45 IAW the Student/Instructor Evaluation Plan Met all critical performance measures IAW the Student/Instructor Evaluation Plan.					

Cold Weather Indoctrination II						
Individual Camoufla	200					
LESSON #	699-80024					
ACTION	Camouflage self and equipment in a snow covered environment					
CONDITION	In any snow covered environment, given individual load bearing equipment,					
	helmet, weapon, ECWCS over whites and camouflage tape					
STANDARD	Camouflaged equipment and weapon without affecting the function. Changed camouflage scheme as conditions changed.					
Firing Techniques						
LESSON #	699-80030					
ACTION	Engage targets with assigned weapons in a snow covered environment					
CONDITION	Given load bearing equipment, helmet, assigned weapon, ECWCS, over white set, skis or snowshoes with ski poles, ahkio sled and M-122 tripod, traversing and elevating mechanism					
STANDARD	Soldier: - engaged targets from a standing, kneeling and prone position on skis and snowshoes engaged targets using crew served weapons.					
Fighting Positions						
LESSON #	699-80029					
ACTION	Construct a fighting position in a snow covered environment.					
CONDITION	Given load bearing equipment, helmet, personal weapon, appropriate clothing, a specific location with trees able to support a wall, a sector of fire, snow, logs, binding materials, and pioneer tools. A location for ice crete will be furnished if it is necessary to produce ice crete blocks. This location will have a water source, gravel source, forms of uniform size and snow.					
STANDARD	Soldier: - Constructed a fighting position wide enough for you, your battle buddy and all your equipment Ensured that fire can be placed into your assigned sector of fire. The position has front, side, rear and overhead cover.					
Tactical Bivouac						
LESSON #	699-80028					
ACTION	Conduct operation of a patrol base in cold regions					
CONDITION	In a snow covered environment with temperatures of 10 degrees F or colder, given the ECWCS, other issued cold weather clothing items, issued cold weather sleep system with insulating pad, other personal equipment prescribed by unit, standard ahkio group or tent and stove normally used by the unit in the field					
STANDARD	Unit: - established and operated from patrol base(s) for one night met all critical performance measures IAW the student/instructor evaluation plan Soldier: - did not sustain any cold weather injuries met all critical performance measures IAW the student/instructor					
	evaluation plan					

LESSON #	699-80027
ACTION	Utilize improvised shelters
CONDITION	In a snow covered environment with temperatures of 10 degrees F or colder, given a bow saw, parachute, 100 feet of 550-cord (thermal shelter only), shovel(s), ECWCS, other issued cold weather clothing items, issued cold weather sleep system with insulating pad and other equipment prescribed by unit
STANDARD	Soldier: - constructed an improvised shelter bivouacked in the shelter for approximately 8 hours without the aid of an external heat source did not receive a cold weather injury during the bivouac met all critical performance measures IAW the student/instructor evaluation plan (see below).
Snowshoeing	
ACTION	Move over snow on snowshoes
CONDITION	Given the military snowshoe with bindings, ski poles and vapor barrier boots, rucksack (with a minimum load of sleeping bag, sleeping pad, extra pair of socks, extra pair of mitten inserts, additional packing list items may be prescribed by unit), ECWCS, other issued cold weather clothing items, ballistic helmet, LCE with 2 quarts of water, weapon and a 5 kilometer snow-covered course with varied terrain
STANDARD	Soldier: - completed a 5 kilometer snowshoe movement did not sustain a cold weather injury met all critical performance measures IAW the student/instructor evaluation plan.
Sled Hauling (Thi	is lesson is optional)
LESSON#	699-80022
ACTION	Haul the scow-sled (ahkio) using skis and/or snowshoes
CONDITION	Given a sled-scow (ahkio), 4 traces, and harnesses in a field environment on snow covered terrain
STANDARD	Unit: - hauled the scow sled over a designated route using skis and/or snowshoes.
Skiing (This lesse	·
LESSON #	699-80020
ACTION	Move over snow on skis
CONDITION	Given the military ski, NATO bindings, ski poles and vapor barrier boots (or other appropriate ski equipment as prescribed by unit), rucksack (with a minimum load of sleeping bag, sleeping pad, extra pair of socks, extra pair of mitten inserts and wax kit, additional packing list items may be prescribed by unit), ECWCS, other issued cold weather clothing items, ballistic helmet, LCE with 2 quarts of water, weapon and a 10 kilometer snow-covered course with varied terrain
STANDARD	Soldier: - completed a 10 kilometer ski movement - did not sustain a cold weather injury - met all critical performance measures IAW the student/instructor evaluation plan

- (4) Units may add training to the ALIT program that is specific to individual job functions (e.g. a unit may use a different shelter/stove system in the field or may want to train aircraft refueling procedures in the cold weather environment). Trainers should develop their own lesson plans based upon appropriate Army doctrine, technical manuals or equipment instruction manuals.
- e. ALIT trainers must be graduates of the Cold Weather Leaders Course (CWLC) or the NWTC Cold Weather Instructor Qualification Course (CWIQC).
- f. ALIT is an annual training requirement for all Soldiers.
- (1) All new arrivals, both enlisted and officer will complete CWI I before participating in any field exercise and CWI I and II before participating in a field exercise during the winter months (01 October through 01 May).
- (2) Soldiers that have attended a CSOC or CWLC in the last 12 months, meet ALIT training requirements. Arctic survival school is *not* a substitute for ALIT training.
- (3) Host units must ensure that units attached for training, but not stationed in Alaska, receive ALIT instruction before field training where temperatures drop below 10 degrees Fahrenheit.
- e. Units provide a memorandum that lists the training conducted during ALIT. Maintain a copy of this memorandum in Soldier training records. This memorandum must be signed by the commander. A sample memorandum is provided at Attachment 4.
- f. Upon completion of training, the Soldier's DA 348 should reflect licensing on appropriate stove(s) (e.g. SHA, H-45, SHC, SHS) or any other special equipment for cold weather that Soldier's were licensed on (e.g. SUSV, plows, snow machines).
- 4. Ski and snowshoe training.
- a. Ski and snowshoe training provide unit commanders with an alternate means of moving troops in a snow covered field environment, provide an alternate means of aerobic physical training during the winter months and allow soldiers to develop confidence in their equipment and their ability to operate in the cold weather environment.
- b. USARAK 350-1, Chapter 4, Paragraph 10 gives specific guidance on conduct of snowshoe or ski PT requirements. Additional guidance is provided in USARAK Pamphlet 385-4, Risk Management for Cold Weather Operations and CG/CofS Policy Letter #0-08, Cold Weather Physical Training Policy. Graduates of the NWTC CWLC also receive training on the conduct of a 10 K ski movement, a 5 k snowshoe movement and downhill ski training.

SUBJECT: ALIT CMP

- 5. References. The publications listed below are key publications to be used in conjunction with the course management plan.
- a. FM 31-70, Basic Cold Weather Manual
- b. FM 31-71, Northern Operations
- c. FM 3-97.6, Mountain Operations
- d. FM 3-97.61, Military Mountaineering
- e. TB Med 508, Prevention and Management of Cold Weather Injuries
- f. USARAK Pamphlet 600-2 (Blue Book), United States Army Alaska Soldiers' Handbook and Standards Guide
- g. USARAK Pamphlet 385-2, Safety –Exercise Handbook
- h. USARAK Pamphlet 385-4, Risk Management for Cold Weather Operations
- i. CG/CofS Policy Letter #0-14, Fuel Fired Space Heater Safety
- j. CG/CofS Policy Letter #0-08, Cold Weather Physical Training Policy
- 6. Point of Contact for this course is the Training Administrator/Course Manager, Fort Wainwright, Alaska, at 907-353-1165 or peter.smith@us.army.mil.

ANTHONY R. ELY MAJ, QM Commandant

EFFECTIVE PERIOD OF SCHEDULE FROM THRU			SAMPLE TRAINING	SCHEDULE			PREPARATION DATE
				UNIT			
DATE	DATE TIME SUBUNIT		MISSION	TRAINERS	LOCATION	UNIFORM	NOTES / REFERENCES
DAY 1	0630	ALIT	Formation	1SG	UNIT	DUTY 1	
	0630-0730	ALIT	Cold Weather PT Policy Review/ALIT LAYOUT	ALL ALIT CADRE	UNIT	DUTY 1	CG/COFS POLICY LETTER
	0900-0930	ALIT	Introduction to ALIT	NCOIC	CLASSROOM	DUTY 1	#0-08: COLD WEATHER
	0930-1030	ALIT	Characteristics of Cold Regions (Terrain and Weather)	ALL ALIT CADRE	CLASSROOM	DUTY 1	PHYSICAL TRAINING POLIC
	1030-1130	ALIT	Cold Weather and Mountain Medical Considerations	ALL ALIT CADRE	CLASSROOM	DUTY 1	
	1130-1300	ALIT	Lunch				
	1300-1400	ALIT	Wear cold weather clothing and equipment	ALL ALIT CADRE	CLASSROOM	DUTY 1	
	1400-1500	ALIT	Manage risk in the cold weather environment	ALL ALIT CADRE	CLASSROOM	DUTY 1	USARAK PAM 385-4
	1500-1800	ALIT	Conduct tent and stove drill/Tactical bivouac	ALL ALIT CADRE	OUTDOORS	DUTY 3	
	1800-1900	ALIT	DINNER/PERSONAL HYGIENE	ALL ALIT CADRE	OUTDOORS	DUTY 3	MCW DINNER
	1900-1930	ALIT	Fit snowshoes	ALL ALIT CADRE	OUTDOORS	DUTY 3	
	1930-2200	ALIT	H-45 or other Army Approved Heater Training	ALL ALIT CADRE	OUTDOORS	DUTY 3	ALIT CADRE MUST BE CWL
	2200-2400	ALIT	Heated shelter bivouac/field sanitation	ALL ALIT CADRE	OUTDOORS	DUTY 3	GRADUATES
							STUDENT TO INSTRUCTOR RATIO MUST NOT EXCEED 9:1
DAY 2	0001-0500	ALIT	Heated shelter bivouac	ALL ALIT CADRE	OUTDOORS	DUTY 3	MCW BREAKFAST
	0500-0630	ALIT	First Call/Cold Weather Injury Checks/Strike Tent	ALL ALIT CADRE	OUTDOORS	DUTY 2	MEDICS
	0630-0730	ALIT	Snowshoe techniques/pt	ALL ALIT CADRE	OUTDOORS	DUTY 3	
	0730-0900	ALIT	Personal hygiene	ALL ALIT CADRE		DUTY 1	
	0900-1000	ALIT	Plan for over snow movement	ALL ALIT CADRE	CLASSROOM	DUTY 1	
	1000-1130		Effects of cold on military equipment	ALL ALIT CADRE	CLASSROOM	DUTY 1	
	1130-1300	ALIT	Lunch	ALL ALIT CADRE		DUTY 3	HEATED SHELTER
	1300-1430	ALIT	Individual camouflage, firing techniques and fighting posn.	ALL ALIT CADRE	CLASSROOM	DUTY 2	AVAILABLE FOR REMAINDE OF TRAINING
	1430-1800	ALIT	Construct an improvised shelter/stove licensing	ALL ALIT CADRE	OUTDOORS	DUTY 3	MCW DINNER
	1800-1900	ALIT	Dinner/personal hygiene	ALL ALIT CADRE		DUTY 3	
	1900-2200	ALIT	Stove licensing	ALL ALIT CADRE	OUTDOORS	DUTY 3	
	2200-2400		Unheated shelter bivouac		OUTDOORS	DUTY 3	
		•	1		•		

WEEK		SAMPLE TRAINING SCHEDULE						PREPARATION DATE	
EFFECTIVE	PERIOD OF	SCHEDULE		UNIT					
FROM THRU									
			•		•				
DATE	TIME	SUBUNIT		MISSION	TRAINERS	LOCATION	UNIFORM	NOTES / REFERENCES	
DAY 3	0001-0500	ALIT	Unheated shelter bivouac		ALL ALIT CADRE	OUTDOORS	DUTY 3	MCW Breakfast	
	0500-0630	ALIT	First Call/Break down/CWI checks/ rep for movement		ALL ALIT CADRE	OUTDOORS	DUTY 3	MEDICS	
	0630-1130	ALIT	5k snowshoe march		ALL ALIT CADRE	OUTDOORS	DUTY 3	USARAK 350-1	
	1130-1300	ALIT	Personal Hygiene/Lunch		ALL ALIT CADRE		DUTY 1		
	1300-1700	ALIT	Recovery/ALIT Gra	aduation	NCOIC/ALL ALIT CADRE	UNIT	DUTY 1		

	WINTER UNIFORM SOP (01 OCT – 30 APR)				
DUTY 1	ACU/BDU ICW or equivalent cold weather boot, BALACLAVA, POLYPROPYLENE AS REQUIRED, CONTACT GLOVES (as a minimum), ARCTIC MITTENS CARRIED				
DUTY 2	GORTEX TROUSERS & PARKA W/ RUFF, POLYPROPYLENE, BALACLAVA, VAPOR BARRIER (VB) BOOTS, TRIGGER FINGER MITTENS W/ INSERTS, LBV AND BALLISTIC HELMET, OVERWHITES WORN IAW ALIT CADRE GUIDANCE, ARCTIC MITTENS AND BLACK GORTEX GLOVES CARRIED OR WORN AS REQUIRED				
DUTY 3	SAME AS DUTY 2; ADD RUCKSACK WITH ISSUED SLEEP SYSTEM, POLYPAD, EXTRA SOCKS, POLYPROPYLENE, SQUAD STOVE WITH FUEL, ISSUED MEALS, FLAHLIGHT OR HEADLAMP, EXTRA BATTERIES, 2 QUART CANTEEN, PILE JACKET AND BIBS (or equivalent), 100' OF 550 CORD, CONTACT GLOVES, BLACK GORTEX GLOVES, ARCTIC MITTENS, PERSONAL HYGIENE ARTICLES, OTHER EQUIPMENT DICATED BY UNIT				
DUTY 4	COMPLETE WINTER PT UNIFORM, APFU TOP & BOTTOM, BALACLAVA, BLACK GLOVES, TRIGGER FINGER MITTENS, ARCTIC MITTENS, REFLECTIVE BELT				

ABBREVIATIONS
FWA FORT WAINWRIGHT

COMMANDERS SIGNATURE BLOCK

Attachment 2: Packing List

ALIT Packing List Required Items

Qty Item Description
 Bag, Sleeping MSS or Type II Extreme Cold
 Mat, Sleeping (Poly Pad recommended)
1 Frame, Field Pack
1 Field Pack, ALICE (Large)
1 Canteen 2 Qt w/ Carrier
2 Canteen, 1 Qt w/ Cup and Carrier
1 E-Tool w/ Carrier
2 Poncho
1 Liner, Poncho
1 Kevlar w/ Camo Cover
1 LBV (worn IAW your Unit's SOP) 100
Bear Suit Top) ft Cord, Nylon (550)
e or Bear Suit Top) 2 Towels
Personal Hygiene Articles
T orosinal riggione / titlolos
Tube of Chapstick
Prescription Medications**
Prescription Eyeglasses**
Sunglasses (inexpensive/durable)
1 ID Tags w/ Chain
•
1 ID Card
ortex) 2 Pocket Knife
1 Cigarette Lighter or Waterproof Matches Flashlight w/ extra Batteries (a headlamp is
1 the best option)
1 Boot care kit Bottom)

Optional Items (Highly Encouraged)

- 1 Army Physical Training Uniform (Complete)
- 1 pr Camp Booties, Insulated
- 1 pr MSR Snow Shoes (If Unit Issued)
- 2 Compression Sacks
- 1 pr Liners, Glove, Polypropylene
- 1 Sewing Kit
- ** As Required

- 1 Ski Goggles w/ Tinted Double-pane Lens
- 1 Drawers, Polypropylene, Lightweight
- 1 Undershirt, Polypropylene, Lightweight
- 4 pr Socks, Polypropylene
- 1 Foot Powder



DEPARTMENT OF THE ARMY

Unit Name Unit Address FORT WAINWRIGHT, ALASKA 99703-9900

Unit Office Symbol	DATE
MEMORANDUM FOR RECORD	
SUBJECT: ALIT Record of Training	

1. SPC Dude, Daniel, 000-00-0000 has successfully completed training on the following lessons/equipment:

Lesson/Equipment	DATE
Licensed on Space Heater Arctic	
Licensed on H-45	
Licensed on Army Approved Heater (List Type)	
Bivouac in heated shelter (overnight)	
Bivouac in an improvised shelter (overnight)	
Characteristics of Cold Regions	
Cold Weather and Mountain Medical Considerations	
Cold Weather Clothing and Equipment	
Risk Management	
Snowshoe training	
Planning Considerations for Over Snow Movement	
Effects of Cold on Military Equipment	
Tent and Stove Drill	
Individual Camouflage	
Firing Techniques	
Fighting Positions	
Ski Training (optional event)	
Sled Hauling (optional event)	
5 K snowshoe march	

2.	The bivouacs	were conducted	at a low	temperature of	of on	
----	--------------	----------------	----------	----------------	-------	--

- 3. Add above listed stoves to the soldiers DD 348.
- 4. POC is the undersigned at 353-###.

DUDLEY X. SMITH SSG, USA ALIT NCOIC

Attachment 4: Equipment and Resources Recommended:

Item	Number/Size	Remarks
Classroom	1 to accommodate students	1 instructor per 25 students for classroom instruction
Projection Screen	1	
Multimedia	1	Download all lessons and PowerPoint presentations at
Computer and		http://www.wainwright.army.mil/nwtc/default.htm
projector		
USARAK	1 per student	http://www.usarak.army.mil/publications/385Series_Safety.htm
Pamphlet 385-4		
CG/CofS Policy	1 per student	Download at http://www.usarak.army.mil/policies/Policies/CG CofS Policy List.htm
Letter #0-08: Cold		
Weather Physical		
Training Policy		
Snowshoes w/	1 pair per student	MSR military w/8 inch flotation tails or Military Magnesium snowshoes
bindings		w/ bindings
Scow-sled, 200	1 per nine	
lbs. capacity	students	
(ahkio)	1 '	
Tent, ten-man	1 per nine	Cut two 6 foot door poles per tent
Arctic, with	students	
telescoping		
pole, pole		
board, and 12		
tent pins SHA with stove	1 per nine	
	students	
board and tripod Five gallon fuel	1 per nine	
_	students	
can Five gallon	1 per nine	
water can	students	
D-handle coal	2 per nine	
shovels	students	
Machetes (with	2 per nine	
sheath)	students	
Squad cook sets	2 per nine students	
Squad stoves	2 per nine students	
Fuel bottles	2 per nine students	
Bow saw	1 per nine	
	students	
Ax	1 per nine	
	students	
Hammers 2 lb.	2 per nine	
	students	
120 ft. rope	1 per nine	
-	students	
Trace, ahkio	3 per nine	
pulling, 9 ft	students	
Tow Rope 27	1 per nine	
feet	students	
Harnesses,	4 per nine	
ahkio towing	students	
Fire	1 per nine	

extinguisher	students	
Lantern,	1 per nine	
gasoline*, with	students	
case		
H-45 Stove w/5	1 per nine students	
gallon fuel can and		
tripod		
Improvised shelter		Enough cut timber to construct thermal shelters; parachute material or ponchos can be
materials		used to cover frame
Meal, Cold	1 per student per	
Weather (MCW)	meal	

DEPARTMENT OF THE ARMY



NORTHERN WARFARE TRAINING CENTER 1060 GAFFNEY ROAD #9900 FORT WAINWRIGHT, ALASKA 99703-9900

APVR-WNW 01 December 2006

MEMORANDUM FOR: Student enrolled in Arctic Light Individual Training (ALIT)

SUBJECT: Student Evaluation Plan (SEP) for ALIT

1. Introduction. ALIT is the United States Army Alaska's Cold Weather Indoctrination (CWI) program. You live, work, and play in one of the harshest environments in the world. You must possess the necessary skills to train to go to war in this demanding environment, despite these conditions. The Arctic Light Individual Training (ALIT) program gives you, regardless of your job, the foundation to successfully work and train in the cold weather environment.

2. ALIT.

- a. *Course Purpose*. To train you in the skills required to successfully train and operate in a cold, snow-covered environment. You will gain confidence in your cold weather clothing and equipment and in your ability to care for yourself in the cold weather environment.
- b. *Course Scope*. Emphasis is placed on the effects of cold on personnel and materiel, recognition, treatment and prevention of cold weather injuries, use of basic cold weather clothing and equipment, winter field-craft, use of cold weather shelters, use of Army approved heaters, and over snow movement techniques. Cold weather risk management procedures are stressed throughout the course of instruction.
- 3. Testing. You will be expected to perform a number of practical exercises throughout this course. You will be evaluated on a GO/NO GO basis. The ALIT Skills Evaluation Guide (see Attachment 1) contains standards you must attain in order to graduate from the course. Not all tests offer re-tests.
- 4. Academic Retraining/Retesting: Retraining and retesting will be conducted IAW the training schedule.
- a. If you fail a test, you will receive re-training from an ALIT instructor.
- b. After re-training is conducted, you will be re-tested.

5. Counseling:

a. Counseling is conducted to provide you with advice and guidance concerning improvement of your current or future performance. It is aimed at providing you positive guidance. Your instructors counsel you to praise and reward good performance, to develop teamwork, to inform

SUBJECT: ALIT SEP

you on how well you are performing, to assist you to reach required standards, to help you resolve personal problems, and to encourage and motivate you to set and work toward achieving personal and professional goals.

- b. Formal and informal counseling will be conducted by the instructors when you are or appear to be having an academic or non-academic problem.
- (1) Formal counseling will be provided when your academic standing falls to borderline failing status or if you fail to comply with standards of academic integrity and conduct. If you are formally counseled, a counseling form will be completed and you will be provided a copy.
- (2) Informal counseling will be provided when an instructor believes it would benefit you or when you ask for assistance.

6.	Testing out.	You may	not test	out on an	y portion	of this c	ourse.
7.	POC this me	morandu	m is				•

Commander's signature block

ALIT SKILLS EVALUATION GUIDE

Name/Rank:		Unit:	Date:
Squad:	_Instructor:		Class #

	SKILL EVALUATION	FIRST	INSTR	RE-	INSTR
	SKILL LVALUATION	EVAL	INITIALS	EVAL	INITIALS
1	Pitch an Arctic ten-man tent	GO		GO	
•	Thom an Arotto ton man tone	NOGO		NOGO	
2	Set up a Space Heater Arctic (SHA)	GO		GO	
	Set up a Space Heater Arctic (SHA)	NOGO		NOGO	
3	Light and Operate a Chase Heater Arctic (CHA)	GO		GO	
3	Light and Operate a Space Heater Arctic (SHA)	NOGO		NOGO	
	Assemble 0 suspets a sussel of sus	GO		GO	
4	Assemble & operate a squad stove	NOGO		NOGO	
_	D' 11 0 1 0114	GO		GO	
5	Disassemble & pack a SHA	NOGO		NOGO	
	A. II	GO		GO	
6	Strike an arctic 10-man tent	NOGO		NOGO	
_	Pack an ahkio sled	GO		GO	
7		NOGO		NOGO	
		GO		GO	
8	Use an H-45 stove (Assembly)	NOGO		NOGO	
		GO		GO	
9	Use an H-45 stove (Light and Operate)	NOGO		NOGO	
	Use an H-45 stove (Shutdown and	GO		GO	
10	Disassemble)	NOGO		NOGO	
	Utilize an improvised shelter (thermal shelter	GO		N/A	
11	recommended 1 night)	NOGO			
	•	GO		GO	
12	Conduct operation of a patrol base in cold regions	NOGO		NOGO	
		GO		N/A	
13	Bivouac in an Arctic 10-man tent (1 night)	NOGO		14//1	
		GO		N/A	
14	Move over snow on snowshoes (5K)	NOGO		14/7	
		NOGO			

PASS FAIL

Instructor Signature	
----------------------	--

^{*} Asterisk next to steps indicate "Critical Performance Measure" Students must meet Critical Performance Measures in order to receive a "GO"

		Coursed Evelvetions				
407	101	Squad Evaluation	11 (A .:		
ACT		Pitch an Arctic Ten-man tent, Set up a Spa				
CON	IDITION	Given a serviceable Ahkio group, complete v				
		large enough to correctly set up the tent and			will be perf	ormed by a
0=4		squad/team of no less than 5 personnel and	evaluated	collectively.		
SIA	NDARD	Squad:				
		- set-up tent and readied stove for operation				
<u> </u>	EDENIOEO	- met all critical performance measures IAW		t/instructor e	valuation pl	an.
KEF	ERENCES	TM 10-8340-222-10 and TM 10-4520-261-12				
		Performance Measures	FIRST	INSTR	RE-	INSTR
4.4	_		EVAL	INITIALS	EVAL	INITIALS
*1	Dug snow	to ground level or packed snow firmly.	GO		GO	
*0	-		NOGO		NOGO	
*2		ent out. Positioned tent so that main door is	GO		GO	
*0		gree angle away from downwind.	NOGO		NOGO	
*3	Zipped bot	h door entrances shut.	GO		GO	
+ 4	Entereded	Ill and an area Para Mada dan da are tha	NOGO		NOGO	
*4		all corner eave lines. Marked spots on the	GO		GO	
		proximately 6 feet (two steps) from each	NOGO		NOGO	
		ne tent. Drove tent pins on the mark. Pins				
*5		htly away from the tent. ix corner eave lines to the pins but left them	GO		GO	
5		ner eave lines are in line with their	NOGO		NOGO	
			NOGO		NOGO	
*6		ding seam of the tent.	GO		GO	
O		and locked center pole to between 6 and 8 d the stud at the top of the pole through the	NOGO		NOGO	
		perforated metal plate at the roof apex. Held	NOGO		NOGO	
		ertically and placed the pole board				
		the base of the pole.				
*7		the corner eave lines. Maintained vertical	GO		GO	
•		pole. Two Soldiers at opposite corner eave	NOGO		NOGO	
		at the same time to tighten. Continued			71000	
	•	process for the remainder of corner eave				
	lines.					
*8		ne corner lines to the same tent pins as the	GO		GO	
		e lines. Corner eave lines and corner lines	NOGO		NOGO	
	must be in	ine with their corresponding seam.				
*9		ots approximately 6 feet from the four eave	GO		GO	
		e tent pins at these marks. Attached and	NOGO		NOGO	
		he four eave lines.				
*10	Anchored t	he two door eave lines. For each door, drove	GO		GO	
	a tent pin a	approximately 6 feet from the tent. Held the	NOGO		NOGO	
	door pole v	vertically about 3 feet from the tent door.				
	Positioned	a clove hitch about five feet up on the door				
		red and tightened the end of the line to the				
	pin. Door h	eight is approximately 4 feet.				
*11		ur ventilators.	GO		GO	
			NOGO		NOGO	
*12	Positioned	fire extinguisher at the center pole.	GO		GO	
			NOGO		NOGO	

*13	Opened and secured stove pipe opening flaps in	GO	GO	
	preparation for using a stove to heat the shelter.	NOGO	NOGO	

		Squad Evaluation				
ACT	ION	Pitch an Arctic Ten-man tent; Set up a Space	Heater A	rctic (SHA)	
CON	IDITION	Given a serviceable Ahkio group, complete warea large enough to correctly set up the tent performed by a squad/team of no less than 5	and stove	group. Thi	s task will	be
STA	NDARD	Squad: - set-up tent and readied stove for operation v - met all critical performance measures IAW tl plan.			evaluation	
REF	ERENCES	TM 10-8340-222-10 and TM 10-4520-261-128	š Ρ			
		Performance Measures	FIRST EVAL	INSTR INITIALS	RE- EVAL	INSTR INITIALS
14*	Stove boar	rd placed on flat surface	GO NOGO		GO NOGO	
15*	Stove door	facing main entrance	GO NOGO		GO NOGO	
16*	Rear door stove body	is reinstalled after removing stove parts from .	GO NOGO		GO NOGO	
17*	cover asse	uels, solid fuel grate is removed and burner embly is installed into the door frame (blocking ehind the front door). Front door is closed.	GO NOGO		GO NOGO	
18*	the burner	uels, burner cover assembly is installed over assembly opening and the solid fuel grate is ith the 'legs' down.	GO NOGO		GO NOGO	
19*		control valve is fully seated on the heater body.	GO NOGO		GO NOGO	
20*		ol outflow hose is properly connected to the ontrol valve.	GO NOGO		GO NOGO	
21*		y hose is properly connected to the fuel flow ve, fuel line is routed away from stove body.	GO NOGO		GO NOGO	
22*	Overflow h	ose is properly connected to the fuel flow ve and routed outside of the tent along a e and below the level of the fuel flow control	GO NOGO		GO NOGO	
23*	Fuel flow o	control valve is in the "OFF" position.	GO NOGO		GO NOGO	
24*		rt of inverted fuel can is between 2 and 3 feet flow control valve.	GO NOGO		GO NOGO	
25*	Lowest pa	rt of inverted fuel can is the fuel can adapter.	GO NOGO		GO NOGO	
26*		eptor loop within 1 foot of fuel can adapter.	GO NOGO		GO NOGO	
27*	Fuel can ir stove.	overted and secured to tripod prior to lighting	GO NOGO		GO NOGO	
28*	Stove pipe	s connected in sequence w/ seams aligned.	GO NOGO		GO NOGO	

29*	Stack cap assembly guy lines secured to tent from 3	GO	GO	
	separate, opposing points.	NOGO	NOGO	
30*	Stove pipe opening flaps rolled up and tied off away from	GO	GO	
	stove pipes.	NOGO	NOGO	

		Individual evaluation				
ACTIO	ON	Light & Operate a Space Heater Arctic				
CONI	DITION	Given a SHA, set up and ready for operation,	and liquid	fuel. This	task will b	ре
		performed and graded individually.				
STAN	IDARD	Stove must be lit and burning steady within 10	minutes.	Met all crit	ical perfo	rmance
		measures IAW the student/instructor evaluation	n plan.			
REFE	RENCES	TM 10-8340-222-10 and TM 10-4520-261-128	kΡ			
		Performance Measures	FIRST	INSTR	RE-	INSTR
*1	Final flame		EVAL	INITIALS	EVAL	INITIALS
1		control valve is set in accordance with outside	GO		GO	
*2	temperatu	FF control knob turned to ON and allow to	NOGO		NOGO	
1 2			GO		GO	
*3		-5 minutes.	NOGO		NOGO	
3	_	p filled using priming valve on the fuel supply	GO NOGO		GO NOGO	
*4	hose.	suincing our is noused into the bottom of	GO		GO	
4	-	oriming cup is poured into the bottom of	NOGO		NOGO	
*5	burner.	nited with a hurning piece of paper or ticque	GO		GO	
5		nited with a burning piece of paper or tissue bottom of the burner.	NOGO		NOGO	
*6			GO		GO	
0	Liu asseiii	oly is closed.	NOGO		NOGO	
*7	As booter:	warms, flow adjustment knob is turned to	GO		GO	
· /	adjust hea		NOGO		NOGO	
*8		t output. It allowed to burn too hot (e.g. cherry red)	GO		GO	
0	Slove is no	or allowed to built too hor (e.g. cherry red)	NOGO		NOGO	
*9	Fuel flow o	control valve must be turned "OFF" prior to	GO		GO	
9	changing f	control valve must be turned "OFF" prior to	NOGO		NOGO	
*10		cupants awake & prepared for emergency exit	GO		GO	
10		eling & re-lighting operations	NOGO		NOGO	
*11		alert and monitoring fuel flow rate and adjusts	GO		GO	
''		ary, when stove is in operation	NOGO		NOGO	
	as 1150535	ary, writer stove is in operation	NOGO		14000	

	Individual evaluation						
ACT	CTION Assemble and Operate a Squad Stove						
CONDITION Given the squad stove and the fuel bottle filled to the proper level with white of						gas, or	
other appropriate fuel. This task will be performed inside the ten-man tent, or						or	
outside in an area sheltered from the wind.							
STANDARD The stove must be placed into operation within 5 minutes. Met all critical							
		performance measures IAW the student/instru	ctor evalu	ation plan.			
REF	ERENCES						
		Performance Measures	FIRST	INSTR	RE-	INSTR	
		EVAL	INITIALS	EVAL	INITIALS		
*1	Pump assembly inserted into fuel bottle & tightened		GO		GO		
	snugly		NOGO		NOGO		
2	Heat reflector properly positioned on stove body				GO		
					NOGO		
3	Stove legs positioned properly into notches of burner		GO		GO		
	housing	NOGO		NOGO			
4	Fuel line inserted into pump w/ gentle pressure &		GO		GO		
	twisting motion		NOGO		NOGO		
*5	Fuel line ca	atch arm secured to pump assembly at notch	GO		GO		
			NOGO		NOGO		
*6	Stove & fu	el bottle placed on a level, non-flammable	GO		GO		
	surface	•	NOGO		NOGO		

EVA	LUATION	Light the squad stove				
		Performance Measures	FIRST EVAL	INSTR INITIALS	RE- EVAL	INSTR INITIALS
1	Fuel bottle	pressurized with 5 to 15 pumps	GO NOGO		GO NOGO	
*2	Fuel valve filled) with	opened - wick saturated (burner cup partially fuel	GO NOGO		GO NOGO	
3	Fuel valve	turned "OFF" during lighting & warm-up	GO NOGO		GO NOGO	
*4		owed to burn until flame begins to diminish & cube warms	GO NOGO		GO NOGO	
5	Valve oper exceed 2 f	ned & adjusted to desired setting (do not ull turns)	GO NOGO		GO NOGO	
6		3 to 4 pumps added when necessary to ottle pressure	GO NOGO		GO NOGO	

NOTE: Too much pressure in fuel bottle causes stove to function poorly w/ sporadic flame. Avoid over-pressuring the fuel bottle with too many pumps.

	Squad Evaluation					
ACT	CTION Disassemble and Pack a Space Heater Arctic					
CON	CONDITION Given an arctic 10-man tent and SHA, properly set up with the stove in operation.					ation.
	This task will be performed by two individuals and evaluated collectively.					
STA	NDARD	The stove must be disassembled and packed				
		the stove body with the stove door closed. All				s for the
		next this and the next two evaluations must be		n 30 minut	es.	
REF	ERENCES	TM 10-8340-222-10 and TM 10-4520-261-128				
		Performance Measures	FIRST EVAL	INSTR INITIALS	RE- EVAL	INSTR INITIALS
*1	Fuel Flow	Control Valve placed in the "OFF" position	GO	INITIALS	GO	INITIALS
	Fuel Flow Control Valve placed in the "OFF" position		NOGO		NOGO	
*2	Fuel can removed from tripod		GO		GO	
_	- I der ean remetted nem uiped		NOGO		NOGO	
*3	Stove is allowed to cool.		GO		GO	
	o otovo io anomou to occi.		NOGO		NOGO	
*4	Fuel lines a	are disconnected and purged of excess fuel	GO		GO	
	The second secon				NOGO	
*5	Fuel flow c	ontrol valve is removed and purged of excess	GO		GO	
	fuel; place valve in the "ON" position for storage		NOGO		NOGO	
*6	Stack cap assembly guy lines untied and stove pipes		GO		GO	
	removed; stack cap guy lines are daisy chained together		NOGO		NOGO	
*7	Stove pipes nested in sequence with seams off-set		GO		GO	
			NOGO		NOGO	
*8	Gravity fee	d adapter removed; fuel can cap re-installed	GO		GO	
			NOGO		NOGO	
*9		ponents are repacked IAW the TM; all	GO		GO	
	component	ts must fit in the stove body	NOGO		NOGO	

		Squad evaluation				
ACT	ION	Strike an arctic 10-man tent				
CON	IDITION	Given a 10-man arctic tent, properly set up wit	th the stov	e removed	l, and the	
		necessary tools for removing tent pins or othe				
STA	NDARD	The tent must be folded for stowage in the ahl			diately re	ady for
		pitching. Tent lines must be managed so they	do not be	come enta	angled.	
REF	ERENCES	TM 10-8340-222-10 and TM 10-4520-261-128				
		Performance Measures	FIRST EVAL	INSTR INITIALS	RE- EVAL	INSTR INITIALS
1	Packed all	personal gear at least 30 minutes prior to	GO	INTIALS	GO	INTITIALS
	striking the		NOGO		NOGO	
2		an fifteen minutes prior to striking the tent,	GO		GO	
_		ed off and allowed to cool, and all personal	NOGO		NOGO	
		d outside of tent in an organized manner.				
3		any tent group equipment and packed in	GO		GO	
	ahkio.		NOGO		NOGO	
*4	Disassemb	oled and packed stove when cool to touch.	GO		GO	
			NOGO		NOGO	
5		rolled and secured corner lines and eave	GO		GO	
		d all eave line tent pins as this is done and	NOGO		NOGO	
		t pins in ahkio.				
*6	Zipped line	er and tent doors fully closed.	GO		GO	
7	D 1 (ant male and male beautiful Oallane administration	NOGO		NOGO	
7		tent pole and pole board. Collapsed pole and	GO		GO	
8		nd the pole board in the ahkio. corner eave lines and fully extended each line.	NOGO GO		NOGO GO	
0		remaining tent pins and placed them in the	NOGO		NOGO	
	ahkio.	emaining tent pins and placed them in the	NOGO		NOGO	
9		tent to clear ice, snow and debris. Spread the	GO		GO	
		pulling on the apex. Folded the tent accordion	NOGO		NOGO	
	style.	paining on the apoxi i class the term accordion	11000			
*10	•	ned the six corner eave lines together.	GO		GO	
		Č	NOGO		NOGO	
11	Folded the	tent in half lengthwise with the daisy chain	GO		GO	
	folded insid	de.	NOGO		NOGO	
12		two shovels opposite one another in the	GO		GO	
		ent. Folded the tent into thirds and placed it	NOGO		NOGO	
	next to the					
13		any remaining equipment and/or trash from	GO		GO	
	the tent site	<u>e.</u>	NOGO		NOGO	

		Carred avaluation				
A O.T.	ION	Squad evaluation				
ACT		Pack an Ahkio Sled		241 11		
CON	DITION	Given a properly folded 10-man arctic tent, SF		with all co	mponents	s, and
0=1		remaining standard equipment and the ahkio s				
STA	NDARD	The ahkio must be packed so it has a low prof			balance i	s low
		and to the rear. All critical performance measured	ures must	be met.		
REF	ERENCES					
		Performance Measures	FIRST EVAL	INSTR INITIALS	RE- EVAL	INSTR INITIALS
1		pins in bottom center of ahkio with the heads	GO		GO	
	• •	ach other. Place hammers on floor of sled on	NOGO		NOGO	
_		of the tent pins, heads opposite one another.				
2	Place bow	saw on top of tent pins.	GO		GO	
			NOGO		NOGO	
3	Place stove	e board on top of bow saw.	GO		GO	
			NOGO		NOGO	
4		extinguisher, center pole, axe, two MSR fuel	GO		GO	
		machetes on either side of the stove board,	NOGO		NOGO	
		ides of the sled, ensuring that the weight is				
	distributed	/				
5		of the stove board, place fuel can and water	GO		GO	
		can opening is up and to the rear and is	NOGO		NOGO	
	•	ged with HAZMAT pads for transport. Water				
		g is down and towards the front of the ahkio.				
6	`	case) is placed in front of stove board,	GO		GO	
	perpendicu	lar to the long axis of the sled. Two cook sets	NOGO		NOGO	
		in front of the lantern.				
7	Place repa	ir kit (ammo can) in front of the lantern. Place	GO		GO	
	squad stov	es on the either side of the sled next to the	NOGO		NOGO	
	cook sets.					
8		oole board in front of the repair kit. Place the	GO		GO	
		pe, traces and harnesses on top of the pole	NOGO		NOGO	
	board.					
9	Place SHA	on top of and slightly to the rear of the stove	GO		GO	
	board.		NOGO		NOGO	
10	Place the to	ent with shovels (so that the apex is toward	GO		GO	
	the front of	sled) on the SHA).	NOGO		NOGO	
11	Fold two ca	anvas ends of ahkio sled over sled contents.	GO		GO	
	Fold sides	of canvas over sled contents.	NOGO		NOGO	
12	Place the t	ripod and door poles on top of canvas	GO		GO	
		dient poles only). The manufactured tripod	NOGO		NOGO	
		sible door poles should be secured inside				
		th the center pole. Secure the contents of				
	sled with th	ne lashing rope from rear to front.				

	ISTR
STANDARD	
- Operated the H-45 IAW the Student/Instructor Evaluation Plan Met all critical performance measures IAW the Student/Instructor Evaluation Plan. REFERENCES TM 10-4520-257-12&P Performance Measures FIRST INSTR EVAL INITIALS EVAL INITIAL	
- Met all critical performance measures IAW the Student/Instructor Evaluation Plan. REFERENCES TM 10-4520-257-12&P	
Evaluation Plan. REFERENCES TM 10-4520-257-12&P	
REFERENCES TM 10-4520-257-12&P Performance Measures FIRST EVAL INITIALS RE-EVAL INITIALS R	
*1 Stove board placed on flat surface. If used in a tent with a floor the base is placed in a sand box or on bricks. *2 Stove components removed from body *3 Burner shell rotated so that pipe nipple aligns with the left side of door opening. *4 Burner shell assembly and adapter ring welded to top is level and fully engaged around the circumference of the heater body base. *5 Superheater and burner cap assemblies and high fire ring are all in place. *6 Fuel flow control valve is properly attached to the stove body. *7 Supply flow control hose assembly, flow control burner hose assembly and overflow hose assembly are properly routed and attached to the fuel flow control. *8 Fuel flow control is in the 'OFF' position. Fuel flow control inverted fuel can is between 2 and 3 feet FIRST INITIALS RE-LINITIALS RO GO NOGO NOGO NOGO NOGO NOGO NOGO NOGO NOGO PO NOGO NOGO NOGO NOGO PO NOGO NOGO PO NOGO NOGO NOGO PO NOGO NOGO PO NOGO NOGO PO NOGO PO NOGO PO NOGO PO NOGO NOGO PO NOGO NOGO PO NOGO PO NOGO PO NOGO PO NOGO PO NOGO NOGO PO NOGO NOGO PO NOGO NOGO PO NOGO NOGO NOGO NOGO	
*1 Stove board placed on flat surface. If used in a tent with a floor the base is placed in a sand box or on bricks. *2 Stove components removed from body *3 Burner shell rotated so that pipe nipple aligns with the left side of door opening. *4 Burner shell assembly and adapter ring welded to top is level and fully engaged around the circumference of the heater body base. *5 Superheater and burner cap assemblies and high fire ring are all in place. *6 Fuel flow control valve is properly attached to the stove body. *7 Supply flow control hose assembly, flow control burner hose assembly and overflow hose assembly are properly routed and attached to the fuel flow control. *8 Fuel flow control is in the 'OFF' position. EVAL INITIALS GO GO NOGO NOGO NOGO NOGO NOGO NOGO N	
a floor the base is placed in a sand box or on bricks. *2 Stove components removed from body *3 Burner shell rotated so that pipe nipple aligns with the left side of door opening. *4 Burner shell assembly and adapter ring welded to top is level and fully engaged around the circumference of the heater body base. *5 Superheater and burner cap assemblies and high fire ring are all in place. *6 Fuel flow control valve is properly attached to the stove body. *7 Supply flow control hose assembly, flow control burner hose assembly and overflow hose assembly are properly routed and attached to the fuel flow control. *8 Fuel flow control is in the 'OFF" position. *8 Lowest part of inverted fuel can is between 2 and 3 feet *6 GO *6 Fuel flow control is in the 'OFF" position. *8 Fuel flow control is inverted fuel can is between 2 and 3 feet *8 GO *9 Lowest part of inverted fuel can is between 2 and 3 feet	
a floor the base is placed in a sand box or on bricks. **2 Stove components removed from body **3 Burner shell rotated so that pipe nipple aligns with the left side of door opening. **4 Burner shell assembly and adapter ring welded to top is level and fully engaged around the circumference of the heater body base. **5 Superheater and burner cap assemblies and high fire ring are all in place. **6 Fuel flow control valve is properly attached to the stove body. **7 Supply flow control hose assembly, flow control burner hose assembly and overflow hose assembly are properly routed and attached to the fuel flow control. **8 Fuel flow control is in the 'OFF" position. **8 Lowest part of inverted fuel can is between 2 and 3 feet **Burner shell rotated so that pipe nipple aligns with the GO RO NOGO **A NOGO **A Supply flow control valve is properly attached to the stove hose assembly are properly routed and attached to the fuel flow control. **B Fuel flow control is in the 'OFF" position. **B Fuel flow control is in the 'OFF" position. **B Lowest part of inverted fuel can is between 2 and 3 feet **B Lowest part of inverted fuel can is between 2 and 3 feet **B Lowest part of inverted fuel can is between 2 and 3 feet **B Lowest part of inverted fuel can is between 2 and 3 feet	
*2 Stove components removed from body *3 Burner shell rotated so that pipe nipple aligns with the left side of door opening. *4 Burner shell assembly and adapter ring welded to top is level and fully engaged around the circumference of the heater body base. *5 Superheater and burner cap assemblies and high fire ring are all in place. *6 Fuel flow control valve is properly attached to the stove body. *7 Supply flow control hose assembly, flow control burner hose assembly and overflow hose assembly are properly routed and attached to the fuel flow control. *8 Fuel flow control is in the 'OFF' position. *8 Lowest part of inverted fuel can is between 2 and 3 feet GO NOGO GO NOGO GO NOGO FO NOGO ROGO NOGO FO NOGO FO NOGO NOGO NOGO NOGO NOGO NOGO NOGO NOGO PO NOGO NOGO NOGO NOGO NOGO PO NOGO NOGO NOGO NOGO PO NOGO NOGO NOGO NOGO NOGO PO NOGO	
*3 Burner shell rotated so that pipe nipple aligns with the left side of door opening. *4 Burner shell assembly and adapter ring welded to top is level and fully engaged around the circumference of the heater body base. *5 Superheater and burner cap assemblies and high fire ring are all in place. *6 Fuel flow control valve is properly attached to the stove body. *7 Supply flow control hose assembly, flow control burner hose assembly and overflow hose assembly are properly routed and attached to the fuel flow control. *8 Fuel flow control is in the 'OFF" position. *8 Lowest part of inverted fuel can is between 2 and 3 feet *6 GO NOGO *9 Lowest part of inverted fuel can is between 2 and 3 feet *8 GO GO NOGO *9 Lowest part of inverted fuel can is between 2 and 3 feet	
*3 Burner shell rotated so that pipe nipple aligns with the left side of door opening. *4 Burner shell assembly and adapter ring welded to top is level and fully engaged around the circumference of the heater body base. *5 Superheater and burner cap assemblies and high fire ring are all in place. *6 Fuel flow control valve is properly attached to the stove body. *7 Supply flow control hose assembly, flow control burner hose assembly and overflow hose assembly are properly routed and attached to the fuel flow control. *8 Fuel flow control is in the 'OFF' position. *8 Lowest part of inverted fuel can is between 2 and 3 feet GO NOGO GO NOGO GO NOGO GO NOGO FO NOGO A GO NOGO GO NOGO FO NOGO GO NOGO GO NOGO FO NOGO GO NOGO FO NOGO GO NOGO FO NOGO FO NOGO GO NOGO FO NOGO FO NOGO GO NOGO FO NOGO NOGO FO NOGO NOGO FO NOGO NOGO NOGO NOGO FO NOGO NOGO NOGO NOGO FO NOGO NO	
left side of door opening. *4 Burner shell assembly and adapter ring welded to top is level and fully engaged around the circumference of the heater body base. *5 Superheater and burner cap assemblies and high fire ring are all in place. *6 Fuel flow control valve is properly attached to the stove body. *7 Supply flow control hose assembly, flow control burner hose assembly and overflow hose assembly are properly routed and attached to the fuel flow control. *8 Fuel flow control is in the 'OFF" position. *8 Lowest part of inverted fuel can is between 2 and 3 feet *6 GO *7 ROGO *8 Lowest part of inverted fuel can is between 2 and 3 feet *8 GO *8 ROGO *9 Lowest part of inverted fuel can is between 2 and 3 feet *8 GO *9 CO **9 Lowest part of inverted fuel can is between 2 and 3 feet *8 GO *8 GO **9 Lowest part of inverted fuel can is between 2 and 3 feet **1 Supply flow control is in the intervent fuel can is between 2 and 3 feet **2 GO **3 Fuel flow control fuel can is between 2 and 3 feet **3 Fuel flow control fuel can is between 2 and 3 feet **3 Fuel flow control fuel can is between 2 and 3 feet **4 Burner shell assembly GO **4 Burner shell assembly and adapter ring welded to top is **6 GO **7 Supply flow control valve is properly attached to the stove **6 Fuel flow control hose assembly, flow control burner **6 Fuel flow control hose assembly are properly **7 NOGO **7 Supply flow control hose assembly are properly **7 NOGO **8 Fuel flow control is in the 'OFF" position. **8 Fuel flow control is in the 'OFF" position. **8 Fuel flow control fuel can is between 2 and 3 feet	
*4 Burner shell assembly and adapter ring welded to top is level and fully engaged around the circumference of the heater body base. *5 Superheater and burner cap assemblies and high fire ring are all in place. *6 Fuel flow control valve is properly attached to the stove body. *7 Supply flow control hose assembly, flow control burner hose assembly and overflow hose assembly are properly routed and attached to the fuel flow control. *8 Fuel flow control is in the 'OFF' position. GO NOGO *9 Lowest part of inverted fuel can is between 2 and 3 feet GO NOGO	
level and fully engaged around the circumference of the heater body base. *5 Superheater and burner cap assemblies and high fire ring are all in place. *6 Fuel flow control valve is properly attached to the stove body. *7 Supply flow control hose assembly, flow control burner hose assembly and overflow hose assembly are properly routed and attached to the fuel flow control. *8 Fuel flow control is in the 'OFF" position. *8 Lowest part of inverted fuel can is between 2 and 3 feet *8 Fuel flow control is inverted fuel can is between 2 and 3 feet *8 GO *8 Fuel flow control is inverted fuel can is between 2 and 3 feet *8 GO *8 Fuel flow control is inverted fuel can is between 2 and 3 feet	
heater body base. *5 Superheater and burner cap assemblies and high fire ring are all in place. *6 Fuel flow control valve is properly attached to the stove body. *7 Supply flow control hose assembly, flow control burner hose assembly and overflow hose assembly are properly routed and attached to the fuel flow control. *8 Fuel flow control is in the 'OFF" position. GO NOGO *9 Lowest part of inverted fuel can is between 2 and 3 feet GO GO NOGO *8 Fuel flow control inverted fuel can is between 2 and 3 feet GO GO NOGO GO NOGO GO NOGO	
ring are all in place. *6 Fuel flow control valve is properly attached to the stove body. *7 Supply flow control hose assembly, flow control burner hose assembly and overflow hose assembly are properly routed and attached to the fuel flow control. *8 Fuel flow control is in the 'OFF" position. *8 Fuel flow control is in the 'OFF" position. *8 Lowest part of inverted fuel can is between 2 and 3 feet *8 GO *8 Fuel flow control is in the 'OFF" position. *8 Fuel flow control is in the 'OFF" position. *8 Fuel flow control is in the 'OFF" position. *8 Fuel flow control is in the 'OFF" position. *8 Fuel flow control is in the 'OFF" position. *8 Fuel flow control is in the 'OFF" position.	
*6 Fuel flow control valve is properly attached to the stove body. *7 Supply flow control hose assembly, flow control burner hose assembly and overflow hose assembly are properly routed and attached to the fuel flow control. *8 Fuel flow control is in the 'OFF" position. GO NOGO *9 Lowest part of inverted fuel can is between 2 and 3 feet GO NOGO GO NOGO	
*6 Fuel flow control valve is properly attached to the stove body. *7 Supply flow control hose assembly, flow control burner hose assembly and overflow hose assembly are properly routed and attached to the fuel flow control. *8 Fuel flow control is in the 'OFF" position. GO NOGO *9 Lowest part of inverted fuel can is between 2 and 3 feet GO NOGO GO NOGO	
body. *7 Supply flow control hose assembly, flow control burner hose assembly and overflow hose assembly are properly routed and attached to the fuel flow control. *8 Fuel flow control is in the 'OFF" position. GO NOGO *9 Lowest part of inverted fuel can is between 2 and 3 feet ONGO NOGO ONGO OO OO OO OO OO	
*7 Supply flow control hose assembly, flow control burner hose assembly and overflow hose assembly are properly routed and attached to the fuel flow control. *8 Fuel flow control is in the 'OFF" position. GO NOGO *9 Lowest part of inverted fuel can is between 2 and 3 feet GO NOGO GO NOGO	
hose assembly and overflow hose assembly are properly routed and attached to the fuel flow control. *8 Fuel flow control is in the 'OFF" position. *9 Lowest part of inverted fuel can is between 2 and 3 feet **OGO **	
routed and attached to the fuel flow control. *8 Fuel flow control is in the 'OFF" position. *9 Lowest part of inverted fuel can is between 2 and 3 feet GO GO NOGO GO NOGO GO O GO O GO O GO O GO O	
*9 Lowest part of inverted fuel can is between 2 and 3 feet GO GO	
*9 Lowest part of inverted fuel can is between 2 and 3 feet	
1 1 1 2 2 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
*10 Lowest part of inverted fuel can is the gravity feed GO GO	
adapter. NOGO NOGO	
*11 Drip interceptor loop within 1 foot of fuel can adapter. GO GO	
NOGO NOGO	
*12 Fuel can inverted and secured to tripod prior to lighting GO GO	
stove. NOGO NOGO	
*13 Stove pipes connected w/ seams aligned. All six pipe GO GO	
sections are used.	
*14 Stack cap assembly guy lines secured to tent from 3 GO GO	
separate, opposing points.	
*15 Stove pipe opening in tent must be serviceable. GO GO	
NOGO NOGO	
*16 Stove pipe opening flaps rolled up and tied off away from GO GO	
stove pipes. NOGO NOGO	

ACT	ION	Use an H-45 stove (light and operate)				
CON	IDITION	Given a serviceable H-45 and an area large e	nough to s	et up the s	stove	
STA	NDARD	Individual soldier:				
		 Operated the H-45 IAW the Student/In- 				
		 Met all critical performance measures 	IAW the St	udent/Inst	ructor	
		Evaluation Plan.				
REF	ERENCES	TM 10-4520-257-12&P				
		Performance Measures	FIRST EVAL	INSTR INITIALS	RE- EVAL	INSTR INITIALS
*1		heater doors are open prior to lighting. Wing	GO		GO	
		ing top of heater to heater body base are	NOGO		NOGO	
	secure.					
*2		ontrol valve is set in accordance with outside	GO		GO	
	temperatur		NOGO		NOGO	
*3		FF control knob turned to ON. Stove is	GO		GO	
		prime for 5-10 minutes with the fuel flow	NOGO		NOGO	
		t knob on the "HI" setting and is then turned				
		osition 3 after 5-10 minutes.				
*4	•	p filled using priming valve on the fuel supply	GO		GO	
	hose.		NOGO		NOGO	
*5		oriming cup is poured into the bottom of	GO		GO	
*0	burner.	20 1 20 1 2 2 2	NOGO		NOGO	
*6		nited with a burning piece of paper or tissue	GO		GO	
+-		bottom of the burner if using diesel or JP5-8.	NOGO		NOGO	
*7		oly is closed (not locked) and fuel flow	GO		GO	
*8		t knob is left at position 3.	NOGO		NOGO	
۳۵		warms, flow adjustment knob is turned to	GO NOGO		GO NOGO	
*9	adjust heat	t output. ot allowed to burn too hot (e.g. cherry red).	GO		GO	
9	Slove is no	or allowed to built too hor (e.g. cherry red).	NOGO		NOGO	
*10	Fuel flow a	ontrol must be turned "OFF" prior to changing	GO		GO	
10	fuel can.	ontrol must be turned OFF prior to changing	NOGO		NOGO	
*11		t be to "cool-to-touch" prior to refueling/ re-	GO		GO	
	lighting	·	NOGO		NOGO	
*12		cupants awake & prepared for emergency exit	GO		GO	
		eling & re-lighting operations	NOGO		NOGO	
*13		alert and monitoring fuel flow rate and	GO		GO	
	adjusted as	s necessary, when stove is in operation	NOGO		NOGO	

ACT	ION	Use an H-45 stove (Shutdown and Disasseml	olv)			
	IDITION	Given a serviceable H-45 and an area large e		et up the s	stove	
	NDARD	Individual soldier:		<u> </u>		
		 Operated the H-45 IAW the Student/In 	structor Ev	aluation P	lan.	
		- Met all critical performance measures				
		Evaluation Plan.				
REF	ERENCES	TM 10-4520-257-12&P				
		Performance Measures	FIRST EVAL	INSTR INITIALS	RE- EVAL	INSTR INITIALS
*1	Fuel flow c	ontrol valve placed in the "OFF" position;	GO	INITIALS	GO	INITIALS
		owed to shut down.	NOGO		NOGO	
*2	Fuel can re	emoved from tripod; gravity feed adapter	GO		GO	
	removed		NOGO		NOGO	
*3		emoved from gravity feed adapter and fuel	GO		GO	
	flow contro		NOGO		NOGO	
*4		are purged of excess fuel; fuel flow control	GO		GO	
		rged of excess fuel; fuel flow control valve	NOGO		NOGO	
		ne "ON" position for storage				
*5	Stove is all	owed to cool.	GO		GO	
			NOGO		NOGO	
*6	Stove pipe	s and stack cap removed.	GO		GO	
*7	10/10/20/20/20	le consedered to a booten about more accord.	NOGO		NOGO	
"/	_	loosened and top heater shell removed;	GO		GO	
*8		Il assembly removed from heater body base.	NOGO		NOGO	
8		ot or ashes removed prior to packing; burner	GO NOGO		GO NOGO	
	cleaning.	nbly returned to heater body base after	NOGO		NOGO	
*9		shell replaced and secured with wing nuts.	GO		GO	
	. 55	chemical and cooling materials	NOGO		NOGO	
*10	Lid opened	I and all components returned to heater body	GO		GO	
	base.	•	NOGO		NOGO	

Note - * denotes a critical task

ACT	ION	Utilize an improvised shelter (thermal shelter)				
In a snow covered environment with temperatures of 10 degrees F or colder, given bow saw, parachute, 100 feet of 550-cord (thermal shelter only), shovel(s), ECWCS other issued cold weather clothing items, issued cold weather sleep system with insulating pad and other equipment prescribed by unit STANDARD Soldier: - constructed an improvised shelter bivouacked in the shelter for approximately 8 hours without the aid of an external heat source did not receive a cold weather injury during the bivouac met all critical performance measures IAW the student/instructor evaluation plan (see below).						
DEE	ERENCES	(see below). N/A				
KEF	LIVEINCES	Performance Measures	FIRST EVAL	INSTR INITIALS	RE- EVAL	INSTR INITIALS
*1	Removed	snow and ice exposing the ground surface.	GO NOGO		GO NOGO	
*2	Constructe	d the framework from available materials.	GO NOGO		GO NOGO	
*3	Ensured from	ont and sides of framework are sloped enough now.	GO NOGO		GO NOGO	
*4		or opening is large enough so a heavily dier will fit through opening.	GO NOGO		GO NOGO	
*5		ing is 1-2 feet above ground to ease entry and	GO NOGO		GO NOGO	
*6	boughs or	amework with poncho, parachute, evergreen other suitable material. Extended material 1-2 d skirt of framework.	GO NOGO		GO NOGO	
*7		aterial with logs rocks or snow, etc.	GO NOGO		GO NOGO	
*8		in material over door opening; material oor frame. Lashed material to door frame for a	GO NOGO		GO NOGO	
*9	Tied a 10-	2in diameter log or bundle of sticks above to support snow load.	GO NOGO		GO NOGO	
*10	Covered e	ntire framework with 8-10 in of snow.	GO NOGO		GO NOGO	
*11		door plug with trash bag or waterproof bag snow or with a rucksack.	GO NOGO		GO NOGO	
12	Low tempe	rature during the bivouac	N/A		N/A	

Note - * denotes a critical task

ACT	TION Conduct operation of a patrol base in cold regions								
CONDITION In a snow covered environment with temperatures of 10 degrees F or colder									
		the ECWCS, other issued cold weather clothing items, issued cold weather sleep							
		system with insulating pad, other personal equipment prescribed by unit, standard							
07.4	ND A DD	ahkio group or tent and stove normally used by the unit in the field							
STANDARD		Unit: - established and operated from patrol base(s) for four nights (one night for CSOC and ALIT) met all critical performance measures IAW the student/instructor evaluation plan. Soldier: - did not sustain any cold weather injuries.							
		 met all critical performance measures IAV plan. 	v the stude	ent/instruct	or evalua	tion			
REFERENCES TASK #071-720-0006									
		Performance Measures	FIRST EVAL	INSTR INITIALS	RE- EVAL	INSTR INITIALS			
*1	Established site.	d a track plan before main body enters the	GO NOGO		GO NOGO				
*2	Selected d positions a track.	GO NOGO		GO NOGO					
*3	Marked all bivouac areas.		GO NOGO		GO NOGO				
*4	Established and maintained a central latrine and waste disposal site.				GO NOGO				
*5	Established a snow collection point for water procurement.		GO NOGO		GO NOGO				
6		Low temperature during the bivouac			N/A				

Note - * denotes a critical task

ACTION		Bivouac in an Arctic 10-man tent							
CONDITION		In a snow covered environment with temperatures of 10 degrees F or colder, given the ECWCS, other issued cold weather clothing items, issued cold weather sleep system with insulating pad, other personal equipment prescribed by unit, standard ahkio group or tent							
		and stove normally used by the unit in the field							
STA	NDARD	Unit utilized an arctic ten-man tent, with an approved Army heater for at least 8 hours (CSOC or ALIT) and for at least 32 hours (CWLC). Met all critical performance measures IAW the student/instructor evaluation plan.							
REF	REFERENCES N/A								
		Performance Measures	FIRST EVAL	INSTR INITIALS	RE- EVAL	INSTR INITIALS			
1*	Soldier utili eight hours	ized a cold weather shelter for a minimum of s.	GO NOGO		GO NOGO				
2*	Soldier utilized an approved Army heater during the bivouac. Note stove type				GO NOGO				
3*	Fire guard is posted, awake and fully dressed if any stove is in operation. Fire guard is licensed on the stove in use.								
4*	All tent occupants were awake & prepared for emergency exit during refueling & re-lighting operations.		GO NOGO		GO NOGO				
5*	Each Soldi	er properly executed roll out drill.	GO NOGO		GO NOGO				
6	Low tempe	rature during the bivouac							

Note - * denotes a critical task

ACT	ION	Move over snow on snowshoes						
CONDITION		Given the military snowshoe with bindings, ski poles and vapor barrier boots, rucksack (with a minimum load of sleeping bag, sleeping pad, extra pair of socks, extra pair of mitten inserts, additional packing list items may be prescribed by unit), ECWCS, other issued cold weather clothing items, ballistic helmet, LCE with 2 quarts of water, weapon and a 5 kilometer snow-covered course with varied terrain						
STANDARD		Soldier: - completed a 5 kilometer snowshoe movement did not sustain a cold weather injury met all critical performance measures IAW the student/instructor evaluation plan.						
REF	ERENCES	NWTC Cold Weather Operations Manual						
	Performance Measures		FIRST EVAL	INSTR INITIALS	RE- EVAL	INSTR INITIALS		
*1	Soldier moved over a 5 kilometer course, with no assistance.		GO NOGO		GO NOGO			
*2	Soldier did	dier did not sustain a cold weather injury			GO NOGO			
3	Time							